



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
1/8	6	0.405	10.29	0.049	1.24	0.19	0.28		10
1/8	6	0.405	10.29	0.057	1.45	0.21	0.32		30
1/8	6	0.405	10.29	0.068	1.73	0.24	0.37	STD	40
1/8	6	0.405	10.29	0.095	2.41	0.31	0.47	XS	80
1/8	6	0.405	10.29	0.124	3.15	0.37	0.55		160
1/8	6	0.405	10.29	0.190	4.83	0.44	0.65	XXS	
1/4	8	0.540	13.72	0.065	1.65	0.33	0.49		10
1/4	8	0.540	13.72	0.073	1.85	0.36	0.54		30
1/4	8	0.540	13.72	0.088	2.24	0.43	0.63	STD	40
1/4	8	0.540	13.72	0.119	3.02	0.54	0.80	XS	80
1/4	8	0.540	13.72	0.145	3.68	0.61	0.91		160
1/4	8	0.540	13.72	0.238	6.05	0.77	1.14	XXS	
3/8	10	0.675	17.1	0.065	1.65	0.42	0.63		10
3/8	10	0.675	17.1	0.073	1.85	0.47	0.70		30
3/8	10	0.675	17.1	0.091	2.31	0.57	0.84	STD	40
3/8	10	0.675	17.1	0.126	3.20	0.74	1.10	XS	80
3/8	10	0.675	17.1	0.158	4.01	0.87	1.30		160
3/8	10	0.675	17.1	0.252	6.40	1.14	1.70	XXS	
1/2	15	0.840	21.34	0.065	1.65	0.54	0.80		5
1/2	15	0.840	21.34	0.083	2.11	0.67	1.00		10
1/2	15	0.840	21.34	0.095	2.41	0.76	1.13		30
1/2	15	0.840	21.34	0.109	2.77	0.85	1.27	STD	40
1/2	15	0.840	21.34	0.147	3.73	1.09	1.62	XS	80
1/2	15	0.840	21.34	0.188	4.78	1.31	1.95		160
1/2	15	0.840	21.34	0.294	7.47	1.72	2.56	XXS	
3/4	20	1.050	26.67	0.065	1.65	0.68	1.02		5
3/4	20	1.050	26.67	0.083	2.11	0.86	1.28		10
3/4	20	1.050	26.67	0.095	2.41	0.97	1.44		30
3/4	20	1.050	26.67	0.113	2.87	1.13	1.68	STD	40
3/4	20	1.050	26.67	0.154	3.91	1.48	2.19	XS	80
3/4	20	1.050	26.67	0.219	5.56	1.95	2.89		160



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
3/4	20	1.050	26.67	0.308	7.82	2.44	3.64	XXS	
1	25	1.315	33.40	0.065	1.65	0.87	1.29		5
1	25	1.315	33.40	0.109	2.77	1.41	2.09		10
1	25	1.315	33.40	0.114	2.90	1.46	2.18		30
1	25	1.315	33.40	0.133	3.38	1.68	2.50	STD	40
1	25	1.315	33.40	0.179	4.55	2.17	3.24	XS	80
1	25	1.315	33.40	0.250	6.35	2.85	4.24		160
1	25	1.315	33.40	0.358	9.09	3.66	5.45	XXS	
1 1/4	32	1.66	42.16	0.065	1.65	1.11	1.65		5
1 1/4	32	1.66	42.16	0.109	2.77	1.81	2.69		10
1 1/4	32	1.66	42.16	0.117	2.97	1.93	2.87		30
1 1/4	32	1.66	42.16	0.140	3.56	2.27	3.39	STD	40
1 1/4	32	1.66	42.16	0.191	4.85	3.00	4.46	XS	80
1 1/4	32	1.66	42.16	0.250	6.35	3.77	5.61		160
1 1/4	32	1.66	42.16	0.382	9.70	5.22	7.77	XXS	
1 1/2	40	1.900	48.26	0.065	1.65	1.28	1.90		5
1 1/2	40	1.900	48.26	0.109	2.77	2.09	3.11		10
1 1/2	40	1.900	48.26	0.125	3.18	2.37	3.54		30
1 1/2	40	1.900	48.26	0.145	3.68	2.72	4.05	STD	40
1 1/2	40	1.900	48.26	0.200	5.08	3.63	5.41	XS	80
1 1/2	40	1.900	48.26	0.281	7.14	4.86	7.24		160
1 1/2	40	1.900	48.26	0.400	10.16	6.41	9.55	XXS	
2	50	2.375	60.32	0.065	1.65	1.61	2.39		5
2	50	2.375	60.32	0.083	2.11	2.03	3.03		
2	50	2.375	60.32	0.109	2.77	2.64	3.93		10
2	50	2.375	60.32	0.125	3.18	3.01	4.48		30
2	50	2.375	60.32	0.141	3.58	3.37	5.01		
2	50	2.375	60.32	0.154	3.91	3.66	5.44	STD	40
2	50	2.375	60.32	0.172	4.37	4.05	6.03		
2	50	2.375	60.32	0.188	4.78	4.40	6.55		
2	50	2.375	60.32	0.218	5.54	5.03	7.48	XS	80



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
2	50	2.375	60.32	0.250	6.35	5.68	8.45		
2	50	2.375	60.32	0.281	7.14	6.29	9.36		
2	50	2.375	60.32	0.344	8.74	7.47	11.12		160
2	50	2.375	60.32	0.436	11.07	9.04	13.45	XXS	
2 1/2	65	2.875	73.02	0.083	2.11	2.48	3.69		5
2 1/2	65	2.875	73.02	0.109	2.77	3.22	4.80		
2 1/2	65	2.875	73.02	0.120	3.05	3.53	5.26		10
2 1/2	65	2.875	73.02	0.125	3.18	3.67	5.48		
2 1/2	65	2.875	73.02	0.141	3.58	4.12	6.13		
2 1/2	65	2.875	73.02	0.156	3.96	4.53	6.74		
2 1/2	65	2.875	73.02	0.172	4.37	4.97	7.40		
2 1/2	65	2.875	73.02	0.188	4.78	5.40	8.04		30
2 1/2	65	2.875	73.02	0.203	5.16	5.80	8.64	STD	40
2 1/2	65	2.875	73.02	0.216	5.49	6.14	9.14		
2 1/2	65	2.875	73.02	0.250	6.35	7.02	10.44		
2 1/2	65	2.875	73.02	0.276	7.01	7.67	11.41	XS	80
2 1/2	65	2.875	73.02	0.375	9.52	10.02	14.91		160
2 1/2	65	2.875	73.02	0.552	14.02	13.71	20.40	XXS	
3	80	3.500	88.90	0.083	2.11	3.03	4.52		5
3	80	3.500	88.90	0.109	2.77	3.95	5.88		
3	80	3.500	88.90	0.12	3.05	4.34	6.46		10
3	80	3.500	88.90	0.125	3.18	4.51	6.72		
3	80	3.500	88.90	0.141	3.58	5.06	7.53		
3	80	3.500	88.90	0.156	3.96	5.58	8.30		
3	80	3.500	88.90	0.172	4.37	6.12	9.11		
3	80	3.500	88.90	0.188	4.78	6.66	9.92		30
3	80	3.500	88.90	0.216	5.49	7.58	11.29	STD	40
3	80	3.500	88.90	0.250	6.35	8.69	12.93		
3	80	3.500	88.90	0.281	7.14	9.67	14.40		
3	80	3.500	88.90	0.300	7.62	10.26	15.27	XS	80
3	80	3.500	88.90	0.438	11.13	14.34	21.35		160



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
3	80	3.500	88.90	0.600	15.24	18.60	27.68	XXS	
3 1/2	90	4.000	101.60	0.083	2.11	3.48	5.18		5
3 1/2	90	4.000	101.60	0.109	2.77	4.53	6.75		
3 1/2	90	4.000	101.60	0.120	3.05	4.98	7.41		10
3 1/2	90	4.000	101.60	0.125	3.18	5.18	7.72		
3 1/2	90	4.000	101.60	0.141	3.58	5.82	8.65		
3 1/2	90	4.000	101.60	0.156	3.96	6.41	9.54		
3 1/2	90	4.000	101.60	0.172	4.37	7.04	10.48		
3 1/2	90	4.000	101.60	0.188	4.78	7.66	11.41		30
3 1/2	90	4.000	101.60	0.226	5.74	9.12	13.57	STD	40
3 1/2	90	4.000	101.60	0.250	6.35	10.02	14.92		
3 1/2	90	4.000	101.60	0.281	7.14	11.17	16.63		
3 1/2	90	4.000	101.60	0.318	8.08	12.52	18.64	XS	80
4	100	4.500	114.30	0.083	2.11	3.92	5.84		5
4	100	4.500	114.30	0.109	2.77	5.12	7.62		
4	100	4.500	114.30	0.120	3.05	5.62	8.37		10
4	100	4.500	114.30	0.125	3.18	5.85	8.71		
4	100	4.500	114.30	0.141	3.58	6.57	9.78		
4	100	4.500	114.30	0.156	3.96	7.24	10.78		
4	100	4.500	114.30	0.172	4.37	7.96	11.85		
4	100	4.500	114.30	0.188	4.78	8.67	12.91		30
4	100	4.500	114.30	0.203	5.16	9.32	13.89		
4	100	4.500	114.30	0.219	5.56	10.02	14.91		
4	100	4.500	114.30	0.237	6.02	10.80	16.08	STD	40
4	100	4.500	114.30	0.250	6.35	11.36	16.91		
4	100	4.500	114.30	0.281	7.14	12.67	18.87		
4	100	4.500	114.30	0.312	7.92	13.97	20.78		
4	100	4.500	114.30	0.337	8.56	15.00	22.32	XS	80
4	100	4.500	114.30	0.438	11.13	19.02	28.32		120
4	100	4.500	114.30	0.531	13.49	22.53	33.54		160
4	100	4.500	114.30	0.674	17.12	27.57	41.03	XXS	



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
5	125	5.563	141.30	0.083	2.11	4.86	7.24		
5	125	5.563	141.30	0.109	2.77	6.36	9.46		5
5	125	5.563	141.30	0.125	3.18	7.27	10.83		
5	125	5.563	141.30	0.134	3.40	7.78	11.56		10
5	125	5.563	141.30	0.156	3.96	9.02	13.41		
5	125	5.563	141.30	0.188	4.78	10.80	16.09		
5	125	5.563	141.30	0.219	5.56	12.51	18.61		
5	125	5.563	141.30	0.258	6.55	14.63	21.77	STD	40
5	125	5.563	141.30	0.281	7.14	15.87	23.62		
5	125	5.563	141.30	0.312	7.92	17.51	26.05		
5	125	5.563	141.30	0.344	8.74	19.19	28.57		
5	125	5.563	141.30	0.375	9.52	20.80	30.94	XS	80
5	125	5.563	141.30	0.500	12.70	27.06	40.28		120
5	125	5.563	141.30	0.625	15.88	32.99	49.12		160
5	125	5.563	141.30	0.750	19.05	38.59	57.43	XXS	
6	150	6.625	168.28	0.083	2.11	5.80	8.65		
6	150	6.625	168.28	0.109	2.77	7.59	11.31		5
6	150	6.625	168.28	0.125	3.18	8.69	12.95		
6	150	6.625	168.28	0.134	3.40	9.30	13.83		10
6	150	6.625	168.28	0.141	3.58	9.77	14.54		
6	150	6.625	168.28	0.156	3.96	10.79	16.05		
6	150	6.625	168.28	0.172	4.37	11.87	17.66		
6	150	6.625	168.28	0.188	4.78	12.94	19.27		
6	150	6.625	168.28	0.203	5.16	13.94	20.76		
6	150	6.625	168.28	0.219	5.56	15.00	22.31		
6	150	6.625	168.28	0.250	6.35	17.04	25.36		
6	150	6.625	168.28	0.280	7.11	18.99	28.26	STD	40
6	150	6.625	168.28	0.312	7.92	21.06	31.32		
6	150	6.625	168.28	0.344	8.74	23.10	34.39		
6	150	6.625	168.28	0.375	9.52	25.05	37.27		
6	150	6.625	168.28	0.432	10.97	28.60	42.56	XS	80



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
6	150	6.625	168.28	0.500	12.70	32.74	48.73		
6	150	6.625	168.28	0.562	14.27	36.43	54.20		120
6	150	6.625	168.28	0.625	15.88	40.09	59.68		
6	150	6.625	168.28	0.719	18.26	45.39	67.56		160
6	150	6.625	168.28	0.750	19.05	47.10	70.11		
6	150	6.625	168.28	0.864	21.95	53.21	79.21	XXS	
6	150	6.625	168.28	0.875	22.22	53.78	80.04		
8	200	8.625	219.08	0.109	2.77	9.92	14.78		5
8	200	8.625	219.08	0.125	3.18	11.36	16.93		
8	200	8.625	219.08	0.148	3.76	13.41	19.97		10
8	200	8.625	219.08	0.156	3.96	14.12	21.01		
8	200	8.625	219.08	0.188	4.78	16.96	25.26		
8	200	8.625	219.08	0.203	5.16	18.28	27.22		
8	200	8.625	219.08	0.219	5.56	19.68	29.28		
8	200	8.625	219.08	0.250	6.35	22.38	33.31		20
8	200	8.625	219.08	0.277	7.04	24.72	36.81		30
8	200	8.625	219.08	0.312	7.92	27.73	41.24		
8	200	8.625	219.08	0.322	8.18	28.58	42.55	STD	40
8	200	8.625	219.08	0.344	8.74	30.45	45.34		
8	200	8.625	219.08	0.375	9.52	33.07	49.20		
8	200	8.625	219.08	0.406	10.31	35.67	53.08		60
8	200	8.625	219.08	0.438	11.13	38.33	57.08		
8	200	8.625	219.08	0.500	12.70	43.43	64.64	XS	80
8	200	8.625	219.08	0.562	14.27	48.44	72.08		
8	200	8.625	219.08	0.594	15.09	51.00	75.91		100
8	200	8.625	219.08	0.625	15.88	53.45	79.58		
8	200	8.625	219.08	0.719	18.26	60.77	90.43		120
8	200	8.625	219.08	0.750	19.05	63.14	93.97		
8	200	8.625	219.08	0.812	20.62	67.82	100.92		140
8	200	8.625	219.08	0.875	22.22	72.49	107.88	XXS	
8	200	8.625	219.08	0.906	23.01	74.76	111.26		160



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
8	200	8.625	219.08	1.000	25.40	81.51	121.32		
8	200	8.625	219.08	1.125	28.58	90.20	134.27		
10	250	10.75	273.0	0.134	3.40	15.21	22.61		5
10	250	10.75	273.0	0.156	3.96	17.67	26.27		
10	250	10.75	273.0	0.165	4.19	18.67	27.78		10
10	250	10.75	273.0	0.188	4.78	21.23	31.62		
10	250	10.75	273.0	0.203	5.16	22.89	34.08		
10	250	10.75	273.0	0.219	5.56	24.65	36.67		
10	250	10.75	273.0	0.250	6.35	28.06	41.76		20
10	250	10.75	273.0	0.279	7.09	31.23	46.49		
10	250	10.75	273.0	0.307	7.80	34.27	51.01		30
10	250	10.75	273.0	0.344	8.74	38.27	56.96		
10	250	10.75	273.0	0.365	9.27	40.52	60.29	STD	40
10	250	10.75	273.0	0.438	11.13	48.28	71.88		
10	250	10.75	273.0	0.500	12.70	54.79	81.53	XS	60
10	250	10.75	273.0	0.562	14.27	61.21	91.05		
10	250	10.75	273.0	0.594	15.09	64.49	95.98		80
10	250	10.75	273.0	0.625	15.88	67.65	100.69		
10	250	10.75	273.0	0.719	18.26	77.1	114.71		100
10	250	10.75	273.0	0.812	20.62	86.26	128.34		
10	250	10.75	273.0	0.844	21.44	89.38	133.01		120
10	250	10.75	273.0	0.875	22.22	92.37	137.42		
10	250	10.75	273.0	0.938	23.83	98.39	146.43		
10	250	10.75	273.0	1.000	25.40	104.23	155.10	XXS	140
10	250	10.75	273.0	1.125	28.58	115.75	172.27		160
10	250	10.75	273.0	1.250	31.75	126.94	188.90		
10	250	10.75	273.0	1.375	34.92	137.80	205.03		
10	250	10.75	273.0	1.438	36.53	143.15	213.03		
12	300	12.75	323.8	0.156	3.96	21.00	31.24		5
12	300	12.75	323.8	0.172	4.37	23.13	34.43		
12	300	12.75	323.8	0.180	4.57	24.19	35.98		10



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
12	300	12.75	323.8	0.188	4.78	25.25	37.61		
12	300	12.75	323.8	0.203	5.16	27.23	40.55		
12	300	12.75	323.8	0.219	5.56	29.34	43.64		
12	300	12.75	323.8	0.250	6.35	33.41	49.71		20
12	300	12.75	323.8	0.281	7.14	37.46	55.76		
12	300	12.75	323.8	0.312	7.92	41.48	61.70		
12	300	12.75	323.8	0.330	8.38	43.81	65.19		30
12	300	12.75	323.8	0.344	8.74	45.62	67.91		
12	300	12.75	323.8	0.375	9.52	49.61	73.79	STD	
12	300	12.75	323.8	0.406	10.31	53.57	79.71		40
12	300	12.75	323.8	0.438	11.13	57.65	85.82		
12	300	12.75	323.8	0.500	12.70	65.48	97.44	XS	
12	300	12.75	323.8	0.562	14.27	73.22	108.93		60
12	300	12.75	323.8	0.625	15.88	81.01	120.59		
12	300	12.75	323.8	0.688	17.48	88.71	132.05		80
12	300	12.75	323.8	0.750	19.05	96.21	143.17		
12	300	12.75	323.8	0.812	20.62	103.63	154.17		
12	300	12.75	323.8	0.844	21.44	107.42	159.87		100
12	300	12.75	323.8	0.875	22.22	111.08	165.26		
12	300	12.75	323.8	0.938	23.83	118.44	176.29		
12	300	12.75	323.8	1.000	25.40	125.61	186.92	XXS	120
12	300	12.75	323.8	1.062	26.97	132.69	197.43		
12	300	12.75	323.8	1.125	28.58	139.81	208.08		140
12	300	12.75	323.8	1.250	31.75	153.67	228.68		
12	300	12.75	323.8	1.312	33.32	160.42	238.69		160
12	300	12.75	323.8	1.375	34.92	167.20	248.78		
12	300	12.75	323.8	1.500	38.10	180.39	268.44		
14	350	14.00	355.6	0.156	3.96	23.09	34.34		5
14	350	14.00	355.6	0.188	4.78	27.76	41.36		
14	350	14.00	355.6	0.203	5.16	29.94	44.59		
14	350	14.00	355.6	0.210	5.33	30.96	46.04		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
14	350	14.00	355.6	0.219	5.56	32.26	48.00		
14	350	14.00	355.6	0.250	6.35	36.75	54.69		10
14	350	14.00	355.6	0.281	7.14	41.21	61.36		
14	350	14.00	355.6	0.312	7.92	45.65	67.91		20
14	350	14.00	355.6	0.344	8.74	50.22	74.76		
14	350	14.00	355.6	0.375	9.52	54.62	81.25	STD	30
14	350	14.00	355.6	0.406	10.31	59.00	87.79		
14	350	14.00	355.6	0.438	11.13	63.50	94.55		40
14	350	14.00	355.6	0.469	11.91	67.84	100.95		
14	350	14.00	355.6	0.500	12.70	72.16	107.40	XS	
14	350	14.00	355.6	0.562	14.27	80.73	120.12		
14	350	14.00	355.6	0.594	15.09	85.13	126.72		60
14	350	14.00	355.6	0.625	15.88	89.36	133.04		
14	350	14.00	355.6	0.688	17.48	97.91	145.76		
14	350	14.00	355.6	0.750	19.05	106.23	158.11		80
14	350	14.00	355.6	0.812	20.62	114.48	170.34		
14	350	14.00	355.6	0.875	22.22	122.77	182.69		
14	350	14.00	355.6	0.938	23.83	130.98	194.98		100
14	350	14.00	355.6	1.000	25.40	138.97	206.84		
14	350	14.00	355.6	1.062	26.97	146.88	218.58		
14	350	14.00	355.6	1.094	27.79	150.93	224.66		120
14	350	14.00	355.6	1.125	28.58	154.84	230.49		
14	350	14.00	355.6	1.250	31.75	170.37	253.58		140
14	350	14.00	355.6	1.406	35.71	189.29	281.72		160
14	350	14.00	355.6	2.000	50.80	256.56	381.85		
14	350	14.00	355.6	2.125	53.98	269.76	401.52		
14	350	14.00	355.6	2.200	55.88	277.51	413.04		
14	350	14.00	355.6	2.500	63.50	307.34	457.43		
16	400	16	406.4	0.165	4.19	27.93	41.56		5
16	400	16	406.4	0.188	4.78	31.78	47.34		
16	400	16.00	406.4	0.203	5.16	34.28	51.06		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
16	400	16.00	406.4	0.219	5.56	36.95	54.96		
16	400	16.00	406.4	0.250	6.35	42.09	62.65		10
16	400	16.00	406.4	0.281	7.14	47.22	70.30		
16	400	16.00	406.4	0.312	7.92	52.32	77.83		20
16	400	16.00	406.4	0.344	8.74	57.57	85.71		
16	400	16.00	406.4	0.375	9.52	62.64	93.18	STD	30
16	400	16.00	406.4	0.406	10.31	67.68	100.71		
16	400	16.00	406.4	0.438	11.13	72.86	108.49		
16	400	16.00	406.4	0.469	11.91	77.87	115.87		
16	400	16.00	406.4	0.500	12.70	82.85	123.31	XS	40
16	400	16.00	406.4	0.562	14.27	92.75	138.00		
16	400	16.00	406.4	0.625	15.88	102.72	152.94		
16	400	16.00	406.4	0.656	16.66	107.60	160.13		60
16	400	16.00	406.4	0.688	17.48	112.62	167.66		
16	400	16.00	406.4	0.750	19.05	122.27	181.98		
16	400	16.00	406.4	0.812	20.62	131.84	196.18		
16	400	16.00	406.4	0.844	21.44	136.74	203.54		80
16	400	16.00	406.4	0.875	22.22	141.48	210.52		
16	400	16.00	406.4	0.938	23.83	151.03	224.83		
16	400	16.00	406.4	1.000	25.40	160.35	238.66		
16	400	16.00	406.4	1.031	26.19	164.98	245.57		100
16	400	16.00	406.4	1.062	26.97	169.59	252.37		
16	400	16.00	406.4	1.125	28.58	178.89	266.30		
16	400	16.00	406.4	1.188	30.18	188.11	280.01		
16	400	16.00	406.4	1.219	30.96	192.61	286.66		120
16	400	16.00	406.4	1.250	31.75	197.10	293.35		
16	400	16.00	406.4	1.438	36.53	223.85	333.21		140
16	400	16.00	406.4	1.594	40.49	245.48	365.38		160
16	400	16.00	406.4	1.750	44.45	266.58	396.77		
18	450	18.00	457.2	0.165	4.19	31.46	46.81		5
18	450	18.00	457.2	0.188	4.78	35.80	53.33		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
18	450	18.00	457.2	0.219	5.56	41.63	61.93		
18	450	18.00	457.2	0.250	6.35	47.44	70.60		10
18	450	18.00	457.2	0.281	7.14	53.23	79.25		
18	450	18.00	457.2	0.312	7.92	58.99	87.75		20
18	450	18.00	457.2	0.344	8.74	64.93	96.66		
18	450	18.00	457.2	0.375	9.52	70.65	105.11	STD	
18	450	18.00	457.2	0.406	10.31	76.36	113.63		
18	450	18.00	457.2	0.438	11.13	82.23	122.44		30
18	450	18.00	457.2	0.469	11.91	87.89	130.79		
18	450	18.00	457.2	0.500	12.70	93.54	139.22	XS	
18	450	18.00	457.2	0.562	14.27	104.76	155.88		40
18	450	18.00	457.2	0.625	15.88	116.09	172.83		
18	450	18.00	457.2	0.688	17.48	127.32	189.56		
18	450	18.00	457.2	0.750	19.05	138.30	205.84		60
18	450	18.00	457.2	0.812	20.62	149.20	222.01		
18	450	18.00	457.2	0.875	22.22	160.18	238.36		
18	450	18.00	457.2	0.938	23.83	171.08	254.68		80
18	450	18.00	457.2	1.000	25.40	181.73	270.48		
18	450	18.00	457.2	1.062	26.97	192.29	286.15		
18	450	18.00	457.2	1.125	28.58	202.94	302.10		
18	450	18.00	457.2	1.156	29.36	208.15	309.64		100
18	450	18.00	457.2	1.188	30.18	213.51	317.82		
18	450	18.00	457.2	1.250	31.75	223.82	333.13		
18	450	18.00	457.2	1.375	34.92	244.37	363.66		120
18	450	18.00	457.2	1.562	39.67	274.48	408.48		140
18	450	18.00	457.2	1.781	45.24	308.79	459.62		160
20	500	20.00	508.0	0.188	4.78	39.82	59.32		5
20	500	20.00	508.0	0.219	5.56	46.31	68.89		
20	500	20.00	508.0	0.250	6.35	52.78	78.56		10
20	500	20.00	508.0	0.281	7.14	59.23	88.19		
20	500	20.00	508.0	0.312	7.92	65.66	97.68		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
20	500	20.00	508.0	0.344	8.74	72.28	107.61		
20	500	20.00	508.0	0.375	9.52	78.67	117.03	STD	20
20	500	20.00	508.0	0.406	10.31	85.04	126.54		
20	500	20.00	508.0	0.438	11.13	91.59	136.38		
20	500	20.00	508.0	0.469	11.91	97.92	145.71		
20	500	20.00	508.0	0.500	12.70	104.23	155.13	XS	30
20	500	20.00	508.0	0.562	14.27	116.78	173.75		
20	500	20.00	508.0	0.594	15.09	123.23	183.43		40
20	500	20.00	508.0	0.625	15.88	129.45	192.73		
20	500	20.00	508.0	0.688	17.48	142.03	211.45		
20	500	20.00	508.0	0.750	19.05	154.34	229.71		
20	500	20.00	508.0	0.812	20.62	166.56	247.84		60
20	500	20.00	508.0	0.875	22.22	178.89	266.20		
20	500	20.00	508.0	0.938	23.83	191.14	284.54		
20	500	20.00	508.0	1.000	25.40	203.11	302.30		
20	500	20.00	508.0	1.031	26.19	209.06	311.19		80
20	500	20.00	508.0	1.062	26.97	215.00	319.94		
20	500	20.00	508.0	1.125	28.58	227.00	337.91		
20	500	20.00	508.0	1.188	30.18	238.91	355.63		
20	500	20.00	508.0	1.250	31.75	250.55	372.90		
20	500	20.00	508.0	1.281	32.54	256.34	381.55		100
20	500	20.00	508.0	1.312	33.32	262.10	390.05		
20	500	20.00	508.0	1.375	34.92	273.76	407.41		
20	500	20.00	508.0	1.500	38.10	296.65	441.52		120
20	500	20.00	508.0	1.750	44.45	341.41	508.15		140
20	500	20.00	508.0	1.969	50.01	379.53	564.85		160
22	550	22.00	558.8	0.188	4.78	43.84	65.31		5
22	550	22.00	558.8	0.219	5.56	50.99	75.86		
22	550	22.00	558.8	0.250	6.35	58.13	86.51		10
22	550	22.00	558.8	0.281	7.14	65.24	97.14		
22	550	22.00	558.8	0.312	7.92	72.34	107.60		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
22	550	22.00	558.8	0.344	8.74	79.64	118.56		
22	550	22.00	558.8	0.375	9.52	86.69	128.96	STD	20
22	550	22.00	558.8	0.406	10.31	93.72	139.46		
22	550	22.00	558.8	0.438	11.13	100.96	150.33		
22	550	22.00	558.8	0.469	11.91	107.95	160.63		
22	550	22.00	558.8	0.500	12.70	114.92	171.04	XS	30
22	550	22.00	558.8	0.562	14.27	128.79	191.63		
22	550	22.00	558.8	0.625	15.88	142.81	212.62		
22	550	22.00	558.8	0.688	17.48	156.74	233.35		
22	550	22.00	558.8	0.750	19.05	170.37	253.58		
22	550	22.00	558.8	0.812	20.62	183.92	273.68		
22	550	22.00	558.8	0.875	22.22	197.60	294.03		60
22	550	22.00	558.8	0.938	23.83	211.19	314.39		
22	550	22.00	558.8	1.000	25.40	224.49	334.12		
22	550	22.00	558.8	1.062	26.97	237.70	353.73		
22	550	22.00	558.8	1.125	28.58	251.05	373.71		80
22	550	22.00	558.8	1.188	30.18	264.31	393.44		
22	550	22.00	558.8	1.250	31.75	277.27	412.68		
22	550	22.00	558.8	1.312	33.32	290.15	431.80		
22	550	22.00	558.8	1.375	34.92	303.16	451.15		100
22	550	22.00	558.8	1.438	36.53	316.08	470.50		
22	550	22.00	558.8	1.500	38.10	328.72	489.25		
22	550	22.00	558.8	1.625	41.28	353.94	526.85		120
22	550	22.00	558.8	1.875	47.62	403.38	600.32		140
22	550	22.00	558.8	2.125	53.98	451.49	672.03		160
24	600	24.00	609.6	0.218	5.54	55.42	82.53		5
24	600	24.00	609.6	0.250	6.35	63.47	94.47		10
24	600	24.00	609.6	0.281	7.14	71.25	106.08		
24	600	24.00	609.6	0.312	7.92	79.01	117.52		
24	600	24.00	609.6	0.344	8.74	86.99	129.51		
24	600	24.00	609.6	0.375	9.52	94.71	140.89	STD	20



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
24	600	24.00	609.6	0.406	10.31	102.40	152.38		
24	600	24.00	609.6	0.438	11.13	110.32	164.27		
24	600	24.00	609.6	0.469	11.91	117.98	175.55		
24	600	24.00	609.6	0.500	12.70	125.61	186.95	XS	
24	600	24.00	609.6	0.562	14.27	140.81	209.51		30
24	600	24.00	609.6	0.625	15.88	156.17	232.52		
24	600	24.00	609.6	0.688	17.48	171.45	255.25		40
24	600	24.00	609.6	0.750	19.05	186.41	277.44		
24	600	24.00	609.6	0.812	20.62	201.28	299.51		
24	600	24.00	609.6	0.875	22.22	216.31	321.87		
24	600	24.00	609.6	0.938	23.83	231.25	344.25		
24	600	24.00	609.6	0.969	24.61	238.57	355.04		60
24	600	24.00	609.6	1.000	25.40	245.87	365.94		
24	600	24.00	609.6	1.062	26.97	260.41	387.52		
24	600	24.00	609.6	1.125	28.58	275.10	409.52		
24	600	24.00	609.6	1.188	30.18	289.71	431.25		
24	600	24.00	609.6	1.219	30.96	296.86	441.80		80
24	600	24.00	609.6	1.250	31.75	304.00	452.46		
24	600	24.00	609.6	1.312	33.32	318.21	473.54		
24	600	24.00	609.6	1.375	34.92	332.56	494.90		
24	600	24.00	609.6	1.438	36.53	346.83	516.27		
24	600	24.00	609.6	1.500	38.10	360.79	536.98		
24	600	24.00	609.6	1.531	38.89	367.74	547.36		100
24	600	24.00	609.6	1.562	39.67	374.66	557.57		
24	600	24.00	609.6	1.812	46.02	429.79	639.62		120
24	600	24.00	609.6	2.062	52.37	483.57	719.68		140
24	600	24.00	609.6	2.344	59.54	542.64	807.68		160
26	650	26.00	660.4	0.250	6.35	68.82	102.42		
26	650	26.00	660.4	0.281	7.14	77.26	115.03		
26	650	26.00	660.4	0.312	7.92	85.68	127.44		10
26	650	26.00	660.4	0.344	8.74	94.35	140.46		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
26	650	26.00	660.4	0.375	9.52	102.72	152.81	STD	
26	650	26.00	660.4	0.406	10.31	111.08	165.29		
26	650	26.00	660.4	0.438	11.13	119.69	178.21		
26	650	26.00	660.4	0.469	11.91	128.00	190.47		
26	650	26.00	660.4	0.500	12.70	136.30	202.86	XS	20
26	650	26.00	660.4	0.562	14.27	152.83	227.39		
26	650	26.00	660.4	0.625	15.88	169.54	252.41		
26	650	26.00	660.4	0.688	17.48	186.16	277.15		
26	650	26.00	660.4	0.750	19.05	202.44	301.12		
26	650	26.00	660.4	0.812	20.62	218.64	325.34		
26	650	26.00	660.4	0.875	22.22	235.01	349.71		
26	650	26.00	660.4	0.938	23.83	251.30	374.10		
26	650	26.00	660.4	1.000	25.40	267.25	397.77		
28	700	28.00	711.2	0.250	6.35	74.16	110.38		
28	700	28.00	711.2	0.281	7.14	83.26	123.97		
28	700	28.00	711.2	0.312	7.92	92.35	137.36		10
28	700	28.00	711.2	0.344	8.74	101.70	151.41		
28	700	28.00	711.2	0.375	9.52	110.74	164.74	STD	
28	700	28.00	711.2	0.406	10.31	119.76	178.21		
28	700	28.00	711.2	0.438	11.13	129.05	192.16		
28	700	28.00	711.2	0.469	11.91	138.03	205.39		
28	700	28.00	711.2	0.500	12.70	146.99	218.77	XS	20
28	700	28.00	711.2	0.562	14.27	164.84	245.26		
28	700	28.00	711.2	0.625	15.88	182.90	272.30		30
28	700	28.00	711.2	0.688	17.48	200.87	299.05		
28	700	28.00	711.2	0.750	19.05	218.48	325.17		
28	700	28.00	711.2	0.812	20.62	236.00	351.17		
28	700	28.00	711.2	0.875	22.22	253.72	377.55		
28	700	28.00	711.2	0.938	23.83	271.36	403.96		
28	700	28.00	711.2	1.000	25.40	288.63	429.59		
28	700	28.00	711.2	1.062	26.97	305.82	455.10		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
30	750	30.00	762.0	0.250	6.35	79.51	118.34		5
30	750	30.00	762.0	0.281	7.14	89.27	132.92		
30	750	30.00	762.0	0.312	7.92	99.02	147.29		10
30	750	30.00	762.0	0.344	8.74	109.06	162.36		
30	750	30.00	762.0	0.375	9.52	118.76	176.67	STD	
30	750	30.00	762.0	0.406	10.31	128.44	191.12		
30	750	30.00	762.0	0.438	11.13	138.42	206.10		
30	750	30.00	762.0	0.469	11.91	148.06	220.32		
30	750	30.00	762.0	0.500	12.70	157.68	234.68	XS	20
30	750	30.00	762.0	0.562	14.27	176.86	263.14		
30	750	30.00	762.0	0.625	15.88	196.26	292.20		30
30	750	30.00	762.0	0.688	17.48	215.58	320.95		
30	750	30.00	762.0	0.750	19.05	234.51	349.04		
30	750	30.00	762.0	0.812	20.62	253.36	377.01		
30	750	30.00	762.0	0.875	22.22	272.43	405.38		
30	750	30.00	762.0	0.938	23.83	291.41	433.81		
30	750	30.00	762.0	1.000	25.40	310.01	461.41		
30	750	30.00	762.0	1.062	26.97	328.53	488.88		
30	750	30.00	762.0	1.125	28.58	347.26	516.93		
30	750	30.00	762.0	1.188	30.18	365.90	544.68		
30	750	30.00	762.0	1.250	31.75	384.17	571.79		
32	800	32.0	813	0.250	6.35	84.85	126.32		
32	800	32.0	813	0.281	7.14	95.28	141.90		
32	800	32.0	813	0.312	7.92	105.69	157.25		10
32	800	32.0	813	0.344	8.74	116.41	173.35		
32	800	32.0	813	0.375	9.52	126.78	188.64	STD	
32	800	32.0	813	0.406	10.31	137.12	204.09		
32	800	32.0	813	0.438	11.13	147.78	220.10		
32	800	32.0	813	0.469	11.91	158.08	235.29		
32	800	32.0	813	0.500	12.70	168.37	250.65	XS	20
32	800	32.0	813	0.562	14.27	188.87	281.09		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
32	800	32.0	813	0.625	15.88	209.62	312.17		30
32	800	32.0	813	0.688	17.48	230.29	342.94		40
32	800	32.0	813	0.750	19.05	250.55	373.00		
32	800	32.0	813	0.812	20.62	270.72	402.94		
32	800	32.0	813	0.875	22.22	291.14	433.33		
32	800	32.0	813	0.938	23.83	311.47	463.78		
32	800	32.0	813	1.000	25.40	331.39	493.35		
32	800	32.0	813	1.062	26.97	351.23	522.80		
32	800	32.0	813	1.125	28.58	371.31	552.88		
32	800	32.0	813	1.188	30.18	391.30	582.64		
32	800	32.0	813	1.250	31.75	410.90	611.72		
34	850	34.0	864	0.250	6.35	90.20	134.31		
34	850	34.0	864	0.281	7.14	101.29	150.88		
34	850	34.0	864	0.312	7.92	112.36	167.21		10
34	850	34.0	864	0.344	8.74	123.77	184.34		
34	850	34.0	864	0.375	9.52	134.79	200.61	STD	
34	850	34.0	864	0.406	10.31	145.80	217.06		
34	850	34.0	864	0.438	11.13	157.14	234.10		
34	850	34.0	864	0.469	11.91	168.11	250.27		
34	850	34.0	864	0.500	12.70	179.06	266.63	XS	20
34	850	34.0	864	0.562	14.27	200.89	299.04		
34	850	34.0	864	0.625	15.88	222.99	332.14		30
34	850	34.0	864	0.688	17.48	245.00	364.92		40
34	850	34.0	864	0.750	19.05	266.58	396.96		
34	850	34.0	864	0.812	20.62	288.08	428.88		
34	850	34.0	864	0.875	22.22	309.84	461.28		
34	850	34.0	864	0.938	23.83	331.52	493.75		
34	850	34.0	864	1.000	25.40	352.77	525.30		
34	850	34.0	864	1.062	26.97	373.94	556.73		
34	850	34.0	864	1.125	28.58	395.36	588.83		
34	850	34.0	864	1.188	30.18	416.70	620.60		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
34	850	34.0	864	1.250	31.75	437.62	651.65		
36	900	36.0	914	0.250	6.35	95.54	142.14		
36	900	36.0	914	0.281	7.14	107.30	159.68		
36	900	36.0	914	0.312	7.92	119.03	176.97		10
36	900	36.0	914	0.344	8.74	131.12	195.12		
36	900	36.0	914	0.375	9.52	142.81	212.35	STD	
36	900	36.0	914	0.406	10.31	154.48	229.77		
36	900	36.0	914	0.438	11.13	166.51	247.82		
36	900	36.0	914	0.469	11.91	178.14	264.96		
36	900	36.0	914	0.500	12.70	189.75	282.29	XS	20
36	900	36.0	914	0.562	14.27	212.90	316.63		
36	900	36.0	914	0.625	15.88	236.35	351.73		30
36	900	36.0	914	0.688	17.48	259.71	386.47		
36	900	36.0	914	0.750	19.05	282.62	420.45		40
36	900	36.0	914	0.812	20.62	305.44	454.30		
36	900	36.0	914	0.875	22.22	328.55	488.68		
36	900	36.0	914	0.938	23.83	351.57	523.14		
36	900	36.0	914	1.000	25.40	374.15	556.62		
36	900	36.0	914	1.062	26.97	396.64	589.98		
36	900	36.0	914	1.125	28.58	419.42	624.07		
36	900	36.0	914	1.188	30.18	442.10	657.81		
36	900	36.0	914	1.250	31.75	464.35	690.80		
38	950	38.0	965	0.312	7.92	125.70	186.94		
38	950	38.0	965	0.344	8.74	138.47	206.11		
38	950	38.0	965	0.375	9.52	150.83	224.33	STD	
38	950	38.0	965	0.406	10.31	163.16	242.74		
38	950	38.0	965	0.438	11.13	175.87	261.82		
38	950	38.0	965	0.469	11.91	188.17	279.94		
38	950	38.0	965	0.500	12.70	200.44	298.26	XS	
38	950	38.0	965	0.562	14.27	224.92	334.58		
38	950	38.0	965	0.625	15.88	249.71	371.70		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
38	950	38.0	965	0.688	17.48	274.42	408.46		
38	950	38.0	965	0.750	19.05	298.65	444.41		
38	950	38.0	965	0.812	20.62	322.80	480.24		
38	950	38.0	965	0.875	22.22	347.26	516.62		
38	950	38.0	965	0.938	23.83	371.63	553.11		
38	950	38.0	965	1.000	25.40	395.53	588.57		
38	950	38.0	965	1.062	26.97	419.35	623.90		
38	950	38.0	965	1.125	28.58	443.47	660.01		
38	950	38.0	965	1.188	30.18	467.50	695.77		
38	950	38.0	965	1.250	31.75	491.07	730.74		
40	1000	40.0	1016	0.312	7.92	132.37	196.90		
40	1000	40.0	1016	0.344	8.74	145.83	217.11		
40	1000	40.0	1016	0.375	9.52	158.85	236.30	STD	
40	1000	40.0	1016	0.406	10.31	171.84	255.71		
40	1000	40.0	1016	0.438	11.13	185.24	275.82		
40	1000	40.0	1016	0.469	11.91	198.19	294.92		
40	1000	40.0	1016	0.500	12.70	211.13	314.23	XS	
40	1000	40.0	1016	0.562	14.27	236.93	352.53		
40	1000	40.0	1016	0.625	15.88	263.07	391.67		
40	1000	40.0	1016	0.688	17.48	289.13	430.45		
40	1000	40.0	1016	0.750	19.05	314.69	468.37		
40	1000	40.0	1016	0.812	20.62	340.16	506.17		
40	1000	40.0	1016	0.875	22.22	365.97	544.81		
40	1000	40.0	1016	0.938	23.83	391.68	583.08		
40	1000	40.0	1016	1.000	25.40	416.91	620.51		
40	1000	40.0	1016	1.062	26.97	442.05	657.82		
40	1000	40.0	1016	1.125	28.58	467.52	695.96		
40	1000	40.0	1016	1.188	30.18	492.90	733.73		
40	1000	40.0	1016	1.250	31.75	517.80	770.67		
42	1050	42.0	1067	0.344	8.74	153.18	228.10		
42	1050	42.0	1067	0.375	9.52	166.86	248.27	STD	



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
42	1050	42.0	1067	0.406	10.31	180.52	268.67		
42	1050	42.0	1067	0.438	11.13	194.60	289.82		
42	1050	42.0	1067	0.469	11.91	208.22	309.90		
42	1050	42.0	1067	0.500	12.70	221.82	330.21	XS	
42	1050	42.0	1067	0.562	14.27	248.95	370.48		
42	1050	42.0	1067	0.625	15.88	276.44	411.64		
42	1050	42.0	1067	0.688	17.48	303.84	452.43		
42	1050	42.0	1067	0.750	19.05	330.72	492.33		
42	1050	42.0	1067	0.812	20.62	357.52	532.11		
42	1050	42.0	1067	0.875	22.22	384.67	572.77		
42	1050	42.0	1067	0.938	23.83	411.74	613.05		
42	1050	42.0	1067	1.000	25.40	438.29	652.46		
42	1050	42.0	1067	1.062	26.97	464.76	691.75		
42	1050	42.0	1067	1.125	28.58	491.57	731.91		
42	1050	42.0	1067	1.188	30.18	518.30	771.69		
42	1050	42.0	1067	1.250	31.75	544.52	810.60		
44	1100	44.0	1118	0.344	8.74	160.54	239.09		
44	1100	44.0	1118	0.375	9.52	174.88	260.25	STD	
44	1100	44.0	1118	0.406	10.31	189.20	281.64		
44	1100	44.0	1118	0.438	11.13	203.97	303.82		
44	1100	44.0	1118	0.469	11.91	218.25	324.88		
44	1100	44.0	1118	0.500	12.70	232.51	346.18	XS	
44	1100	44.0	1118	0.562	14.27	260.97	388.42		
44	1100	44.0	1118	0.625	15.88	289.80	431.62		
44	1100	44.0	1118	0.688	17.48	318.55	474.42		
44	1100	44.0	1118	0.750	19.05	346.76	516.29		
44	1100	44.0	1118	0.812	20.62	374.88	558.04		
44	1100	44.0	1118	0.875	22.22	403.38	600.46		
44	1100	44.0	1118	0.938	23.83	431.79	643.03		
44	1100	44.0	1118	1.000	25.40	459.67	684.41		
44	1100	44.0	1118	1.062	26.97	487.47	725.67		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
44	1100	44.0	1118	1.125	28.58	515.63	767.85		
44	1100	44.0	1118	1.188	30.18	543.70	809.65		
44	1100	44.0	1118	1.250	31.75	571.25	850.54		
46	1150	46.0	1168	0.344	8.74	167.89	249.87		
46	1150	46.0	1168	0.375	9.53	182.90	271.99	STD	
46	1150	46.0	1168	0.406	10.31	197.88	294.35		
46	1150	46.0	1168	0.438	11.13	213.33	317.54		
46	1150	46.0	1168	0.469	11.91	228.27	339.56		
46	1150	46.0	1168	0.500	12.70	243.20	361.84	XS	
46	1150	46.0	1168	0.562	14.27	272.98	406.02		
46	1150	46.0	1168	0.625	15.88	303.16	451.20		
46	1150	46.0	1168	0.688	17.48	333.26	495.97		
46	1150	46.0	1168	0.750	19.05	362.79	539.78		
46	1150	46.0	1168	0.812	20.62	392.24	583.47		
46	1150	46.0	1168	0.875	22.22	422.09	627.86		
46	1150	46.0	1168	0.938	23.83	451.85	672.41		
46	1150	46.0	1168	1.000	25.40	481.05	715.73		
46	1150	46.0	1168	1.062	26.97	510.17	758.92		
46	1150	46.0	1168	1.125	28.58	539.68	803.09		
46	1150	46.0	1168	1.188	30.18	569.10	846.86		
46	1150	46.0	1168	1.250	31.75	597.97	889.69		
48	1200	48.0	1219	0.344	8.74	175.25	260.86		
48	1200	48.0	1219	0.375	9.52	190.92	283.96	STD	
48	1200	48.0	1219	0.406	10.31	206.56	307.32		
48	1200	48.0	1219	0.438	11.13	222.70	331.54		
48	1200	48.0	1219	0.469	11.91	238.30	354.54		
48	1200	48.0	1219	0.500	12.70	253.89	377.81	XS	
48	1200	48.0	1219	0.562	14.27	285.00	423.97		
48	1200	48.0	1219	0.625	15.88	316.52	471.17		
48	1200	48.0	1219	0.688	17.48	347.97	517.95		
48	1200	48.0	1219	0.750	19.05	378.83	563.74		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
48	1200	48.0	1219	0.812	20.62	409.61	609.40		
48	1200	48.0	1219	0.875	22.22	440.80	655.81		
48	1200	48.0	1219	0.938	23.83	471.90	702.38		
48	1200	48.0	1219	1.000	25.40	502.43	747.67		
48	1200	48.0	1219	1.062	26.97	532.88	792.84		
48	1200	48.0	1219	1.125	28.58	563.73	839.04		
48	1200	48.0	1219	1.188	30.18	594.50	884.82		
48	1200	48.0	1219	1.250	31.75	624.70	929.62		
52	1300	52.0	1321	0.375	9.52	206.95	307.91		
52	1300	52.0	1321	0.406	10.31	223.93	333.26		
52	1300	52.0	1321	0.438	11.13	241.42	359.54		
52	1300	52.0	1321	0.469	11.91	258.36	384.50		
52	1300	52.0	1321	0.500	12.70	275.27	409.76		
52	1300	52.0	1321	0.562	14.27	309.03	459.86		
52	1300	52.0	1321	0.625	15.88	343.25	511.12		
52	1300	52.0	1321	0.688	17.48	377.39	561.93		
52	1300	52.0	1321	0.750	19.05	410.9	611.66		
52	1300	52.0	1321	0.812	20.62	444.33	661.27		
52	1300	52.0	1321	0.875	22.22	478.21	711.70		
52	1300	52.0	1321	0.938	23.83	512.01	762.33		
52	1300	52.0	1321	1.000	25.40	545.19	811.57		
52	1300	52.0	1321	1.062	26.97	578.29	860.69		
52	1300	52.0	1321	1.125	28.58	611.84	910.93		
52	1300	52.0	1321	1.188	30.18	645.30	960.74		
52	1300	52.0	1321	1.250	31.75	678.15	1009.49		
56	1400	56.0	1422	0.375	9.52	222.99	331.62		
56	1400	56.0	1422	0.406	10.31	241.29	358.94		
56	1400	56.0	1422	0.438	11.13	260.15	387.26		
56	1400	56.0	1422	0.469	11.91	278.41	414.17		
56	1400	56.0	1422	0.500	12.70	296.65	441.39		
56	1400	56.0	1422	0.562	14.27	333.06	495.41		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
56	1400	56.0	1422	0.625	15.88	369.97	550.67		
56	1400	56.0	1422	0.688	17.48	406.80	605.46		
56	1400	56.0	1422	0.750	19.05	442.97	659.11		
56	1400	56.0	1422	0.812	20.62	479.05	712.63		
56	1400	56.0	1422	0.875	22.22	515.63	767.05		
56	1400	56.0	1422	0.938	23.83	552.12	821.68		
56	1400	56.0	1422	1.000	25.40	587.95	874.83		
56	1400	56.0	1422	1.062	26.97	623.70	927.86		
56	1400	56.0	1422	1.125	28.58	659.94	982.12		
56	1400	56.0	1422	1.188	30.18	696.10	1035.91		
56	1400	56.0	1422	1.250	31.75	731.60	1088.57		
60	1500	60.0	1524	0.375	9.52	239.02	355.57		
60	1500	60.0	1524	0.406	10.31	258.65	384.87		
60	1500	60.0	1524	0.438	11.13	278.88	415.26		
60	1500	60.0	1524	0.469	11.91	298.47	444.13		
60	1500	60.0	1524	0.500	12.70	318.03	473.34		
60	1500	60.0	1524	0.562	14.27	357.09	531.30		
60	1500	60.0	1524	0.625	15.88	396.70	590.62		
60	1500	60.0	1524	0.688	17.48	436.22	649.44		
60	1500	60.0	1524	0.750	19.05	475.04	707.03		
60	1500	60.0	1524	0.812	20.62	513.77	764.50		
60	1500	60.0	1524	0.875	22.22	553.04	822.94		
60	1500	60.0	1524	0.938	23.83	592.23	881.63		
60	1500	60.0	1524	1.000	25.40	630.71	938.73		
60	1500	60.0	1524	1.062	26.97	669.11	995.71		
60	1500	60.0	1524	1.125	28.58	708.05	1054.01		
60	1500	60.0	1524	1.188	30.18	746.90	1111.83		
60	1500	60.0	1524	1.250	31.75	785.05	1168.44		
64	1600	64.0	1626	0.375	9.52	255.06	379.51		
64	1600	64.0	1626	0.406	10.31	276.01	410.81		
64	1600	64.0	1626	0.438	11.13	297.61	443.25		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
64	1600	64.0	1626	0.469	11.91	318.52	474.09		
64	1600	64.0	1626	0.500	12.70	339.41	505.29		
64	1600	64.0	1626	0.562	14.27	381.12	567.20		
64	1600	64.0	1626	0.625	15.88	423.42	630.56		
64	1600	64.0	1626	0.688	17.48	465.64	693.41		
64	1600	64.0	1626	0.750	19.05	507.11	754.95		
64	1600	64.0	1626	0.812	20.62	548.49	816.37		
64	1600	64.0	1626	0.875	22.22	590.46	878.84		
64	1600	64.0	1626	0.938	23.83	632.34	941.57		
64	1600	64.0	1626	1.000	25.40	673.47	1002.62		
64	1600	64.0	1626	1.062	26.97	714.52	1063.55		
64	1600	64.0	1626	1.125	28.58	756.15	1125.90		
64	1600	64.0	1626	1.188	30.18	797.69	1187.74		
64	1600	64.0	1626	1.250	31.75	838.50	1248.30		
68	1700	68.0	1727	0.469	11.91	338.57	503.75		
68	1700	68.0	1727	0.500	12.70	360.79	536.92		
68	1700	68.0	1727	0.562	14.27	405.15	602.74		
68	1700	68.0	1727	0.625	15.88	450.15	670.12		
68	1700	68.0	1727	0.688	17.48	495.06	736.95		
68	1700	68.0	1727	0.750	19.05	539.18	802.40		
68	1700	68.0	1727	0.812	20.62	583.21	867.73		
68	1700	68.0	1727	0.875	22.22	627.87	934.18		
68	1700	68.0	1727	0.938	23.83	672.45	1000.92		
68	1700	68.0	1727	1.000	25.40	716.23	1065.89		
68	1700	68.0	1727	1.062	26.97	759.93	1130.73		
68	1700	68.0	1727	1.125	28.58	804.26	1197.09		
68	1700	68.0	1727	1.188	30.18	848.49	1262.92		
68	1700	68.0	1727	1.250	31.75	891.95	1327.39		
72	1800	72.0	1829	0.500	12.70	382.17	568.87		
72	1800	72.0	1829	0.562	14.27	429.18	638.64		
72	1800	72.0	1829	0.625	15.88	476.87	710.06		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
72	1800	72.0	1829	0.688	17.48	524.48	780.92		
72	1800	72.0	1829	0.750	19.05	571.25	850.32		
72	1800	72.0	1829	0.812	20.62	617.93	919.60		
72	1800	72.0	1829	0.875	22.22	665.29	990.08		
72	1800	72.0	1829	0.938	23.83	712.55	1060.87		
72	1800	72.0	1829	1.000	25.40	758.99	1129.78		
72	1800	72.0	1829	1.062	26.97	805.34	1198.57		
72	1800	72.0	1829	1.125	28.58	852.36	1268.98		
72	1800	72.0	1829	1.188	30.18	899.29	1338.83		
72	1800	72.0	1829	1.250	31.75	945.40	1407.25		
76	1900	76.0	1930	0.500	12.70	403.55	600.50		
76	1900	76.0	1930	0.562	14.27	453.21	674.18		
76	1900	76.0	1930	0.625	15.88	503.60	749.62		
76	1900	76.0	1930	0.688	17.48	553.90	824.45		
76	1900	76.0	1930	0.750	19.05	603.32	897.77		
76	1900	76.0	1930	0.812	20.62	652.65	970.96		
76	1900	76.0	1930	0.875	22.22	702.70	1045.42		
76	1900	76.0	1930	0.938	23.83	752.66	1120.22		
76	1900	76.0	1930	1.000	25.40	801.75	1193.05		
76	1900	76.0	1930	1.062	26.97	850.75	1265.74		
76	1900	76.0	1930	1.125	28.58	900.47	1340.17		
76	1900	76.0	1930	1.188	30.18	950.09	1414.01		
76	1900	76.0	1930	1.250	31.75	998.85	1486.33		
80	2000	80.0	2032	0.562	14.27	477.25	710.08		
80	2000	80.0	2032	0.625	15.88	530.32	789.56		
80	2000	80.0	2032	0.688	17.48	583.32	868.43		
80	2000	80.0	2032	0.750	19.05	635.39	945.69		
80	2000	80.0	2032	0.812	20.62	687.37	1022.83		
80	2000	80.0	2032	0.875	22.22	740.12	1101.81		
80	2000	80.0	2032	0.938	23.83	792.77	1180.17		
80	2000	80.0	2032	1.000	25.40	844.51	1256.94		



ASME B36.10M Steel Pipe Weight Chart

NPS	DN	Outside Diameter		Wall Thickness		Plain End Mass		Identification	Schedule No.
		in	mm	in	mm	lb/ft	kg/m		
80	2000	80.0	2032	1.062	26.97	896.17	1333.59		
80	2000	80.0	2032	1.125	28.58	948.57	1412.06		
80	2000	80.0	2032	1.188	30.18	1000.89	1489.92		
80	2000	80.0	2032	1.250	31.75	1052.30	1566.20		